

DensArmor Plus® Interior Panel

Steel-Framed Wall

5/8" (15.9 mm) **ToughRock® Fireguard®** or 5/8" (15.9 mm) **DensArmor Plus® Fireguard®** interior panels applied vertically or horizontally to one side of 2-1/2" (64 mm), 25-gauge (18 mils) steel studs 24" (610 mm) o.c. with 1" (25.4 mm) Type S drywall screws 8" (203 mm) o.c. at vertical joints and 12" (305 mm) o.c. at intermediate studs when applied vertically to framing, or 8" (203 mm) o.c. when applied horizontally to framing.



Opposite side:

Base layer – 5/8" (15.9 mm) **ToughRock® Fireguard®** or 5/8" (15.9 mm) **DensArmor Plus® Fireguard®** interior panels applied vertically or horizontally to studs with 1" (25.4 mm) Type S drywall screws 8" (203 mm) o.c. at vertical joints and 12" (305 mm) o.c. at intermediate studs when applied vertically to framing, or 8" (203 mm) o.c. when applied horizontally to framing.

Second layer – 5/8" (15.9 mm) **ToughRock® Fireguard®** or 5/8" (15.9 mm) **DensArmor Plus® Fireguard®** interior panels applied vertically or horizontally to studs with 1-5/8" (41 mm) Type S drywall screws 12" (305 mm) o.c.

Face layer – 5/8" (15.9 mm) **ToughRock® Fireguard®** or 5/8" (15.9 mm) **DensArmor Plus® Fireguard®** interior panels applied vertically or horizontally to studs with 2-3/8" (60 mm) Type S drywall screws 8" (203 mm) o.c. at vertical joints and 12" (305 mm) o.c. at intermediate studs when applied vertically to framing, or 8" (203 mm) o.c. applied horizontally to framing. Horizontal joints staggered not less than 6" (152 mm) between layers. When gypsum panels are other than 48" (1219 mm) wide, panels are applied horizontally to the framing. Vertical joints staggered 24" (610 mm) each layer and side.

Sound tested with 2-1/2" (64 mm) fiberglass insulation.



Website: www.gpgypsum.com

Georgia-Pacific Gypsum

133 Peachtree St.
Atlanta, Georgia 30303
PH. 1-(800)-225-6119

DensArmor Plus® Interior Panel

| | | |
|-------------|---------------|-------------------|
| Assembly: | U421-04 | UL U421 |
| Date: | December 2012 | |
| Drawn by: | JAT | Fire Rating: 2 Hr |
| Checked by: | RSS | |