

**ForceField® seam tape** is a pressure sensitive, coated polymeric film used for sealing joints and penetrations in the ForceField air and water barrier system. The tape is minimum 3” wide, 0.003” thick, and has been tested per PSTC 1 (Peel Adhesion for Pressure Sensitive Tapes) and PSTC 31 (Breaking Strength and Elongation of Pressure Sensitive Tapes). Benefits include:

- Seals against air and moisture infiltration
- UV and weather resistant
- Performs in cold weather down to 0° F (-18° C)
- Easy tear edge for fast application
- No applicator tool needed
- No release liner, reducing waste on the jobsite and helping save time during installation

### Size

**Roll:** 3 in. x 180 ft. (76.1 mm x 54.8 m)

**Rolls/Case:** 8

### Specifications

TEST	TYPICAL VALUE* (English)	TYPICAL VALUE* (Metric)	TEST METHOD
Thickness	3.0 mils	0.08 mm	PSTC-133
Peel Adhesion <sup>Δ</sup>			
– to stainless steel	45 oz/in	12.5 N/25 mm	PSTC-101
– to polyethylene	16 oz/in	4.5 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	20 lb/in	90.4 N/25 mm	PSTC-131
Elongation	130%	130%	PSTC-131
WVTR		0.061 perms	ASTM E96
Service Temperature	0 to 185 °F	-17.8 to 85 °C	

<sup>Δ</sup>-20 minute dwell.

\* Typical values are not intended to be used for specification development.

Technical data is believed to be true and accurate.