Georgia-Pacific
# DryMax®
Premium OSB

buildgp.com

**DryMax® Premium OSB** is an excellent choice for sub-floors in residential and light commercial construction applications. Each panel is third-party certified for quality and is rated for Exposure 1 bond durability for protected applications and limited exposure during normal construction delays. DryMax® Premium OSB has exceptionally low thickness swell when exposed to moisture, helping to avoid costly and time-consuming joint sanding, plus an enhanced clear edge seal to help reduce edge swell.

## Available Sizes (sized for 4' x 8')

| | |
|---|---|
| **Square Edge** | 3'-11 7/8" (1.216 m) x 7'-11 7/8" (2.435 m) |
| **Tongue & Groove** | 3'-11 1/2" (1.206 m) x 7'-11 7/8" (2.435 m) |

## Building Code Performance Categories, Panel Thickness

- 3/8 CAT, 0.354" (12.26 mm)
- 19/32 CAT, 0.578" (14.68 mm)
- 23/32 CAT, 0.703" (17.85 mm)

## Specifications

| | |
|---|---|
| **Length/Width Tolerance** | ± 1/16" (± 1.6 mm) |
| **Straightness Tolerance** | ± 1/16" (± 1.6 mm) |
| **Squareness Tolerance** | ± 1/8" (± 3.2 mm) |
| **Testing Agency** | APA®–The Engineered Wood Association |
| **Classification** | **Exposure 1** – OSB suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of mositure on structural performance as may occur due to construction delays, or other conditions of similar severity. |
| **Code Fire Classification** | Class III or C |
| **Flame Spread Rating** | 76-200, smoke-developed index <450 |
| **Building Code Compliance** | PS 2-18; CAN/CSA-0325-21 |

## Other Information

| | |
|---|---|
| **Forestry Certification** | DryMax® Premium OSBpanels are made in compliance with the Sustainable Forestry Initiative® (SFI®) SFI-00007 in the USA and Canada. |
| **Product Warranty** | DryMax® Premium OSB is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at **www.buildgp.com**. |

SUSTAINABLE FORESTRY INITIATIVE
SFI-00007

Georgia-Pacific DryMax® Premium OSB

buildgp.com

**International Shipping**

To prevent the introduction and spread of plant pests, **ISPM 15: International Standards for Phytosanitary Measures**, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance.

**Pallets made with engineered wood, including DryMax® Premium OSB, are exempt from ISPM 15 regulations**. This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing", **www.PerformancePanels.com**).

**Formaldehyde Emissions**

DryMax® Premium OSB contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the **Composite Wood Air Toxic Control Measure (ATCM)** and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the **Manufactured Home Construction and Safety Standards**.

**Manufacturing Locations**

| Location | APA Mill Number | Zip Code | Harvest Radius |
|---|---|---|---|
| Englehart, ONT, CA | 530 | P0J 1H0 | 50 miles |

DryMax, Georgia-Pacific and the DryMax and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC.
APA and Sturd-I-Floor are registered trademarks of APA-The Engineered Wood Association. ©2026 Georgia-Pacific Wood Products LLC. All rights reserved.
WD-DM-CA-USCA-EN-1-R01-102026