



DryMax® Premium OSB is an excellent choice for sub-floors in residential and light commercial construction applications. Each panel is third-party certified for quality and is rated for Exposure 1 bond durability for protected applications and limited exposure during normal construction delays. DryMax® Premium OSB has exceptionally low thickness swell when exposed to moisture, helping to avoid costly and time-consuming joint sanding, plus an enhanced clear edge seal to help reduce edge swell.

Available Sizes (sized for 4' x 8')

Square Edge	3'-11 ⁷ / ₈ " (1.216 m) x 7'-11 ⁷ / ₈ " (2.435 m)
Tongue & Groove	3'-11 ¹ / ₂ " (1.206 m) x 7'-11 ⁷ / ₈ " (2.435 m)

Building Code Performance Categories, Panel Thickness

- 3/8 CAT, 0.354" (12.26 mm)
- 19/32 CAT, 0.578" (14.68 mm)
- 23/32 CAT, 0.703" (17.85 mm)

Specifications

Length/Width Tolerance	± 1/16" (± 1.6 mm)
Straightness Tolerance	± 1/16" (± 1.6 mm)
Squareness Tolerance	± 1/8" (± 3.2 mm)
Testing Agency	APA®-The Engineered Wood Association
Classification	Exposure 1 – OSB suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.
Code Fire Classification	Class III or C
Flame Spread Rating	76-200, smoke-developed index <450
Building Code Compliance	PS 2-18; CAN/CSA-0325-21

Other Information

Product Warranty	DryMax® Premium OSB is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at www.buildgpc.com .
International Shipping	To prevent the introduction and spread of plant pests, ISPM 15: International Standards for Phytosanitary Measures , requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance. Pallets made with engineered wood, including DryMax® Premium OSB, are exempt from ISPM 15 regulations. This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing", www.PerformancePanels.com).



buildgpc.com

Formaldehyde Emissions DryMax® Premium OSB contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the **Composite Wood Air Toxic Control Measure (ATCM)** and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the **Manufactured Home Construction and Safety Standards**.

Manufacturing Locations

Location	APA Mill Number	Zip Code	Harvest Radius
Englehart, ONT, CA	530	POJ 1H0	50 miles

DryMax, Georgia-Pacific and the DryMax and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. APA and Sturd-I-Floor are registered trademarks of APA-The Engineered Wood Association. ©2026 Georgia-Pacific Wood Products LLC. All rights reserved. 082026 Lit. Item # 621515