Georgia-Pacific

DryGuard®

Enhanced OSB

buildgp.com

DryGuard® Enhanced OSB is a multi-layered sub-floor product that has improved moisture resistance throughout the panel plus a black edge seal to help reduce moisture absorption. This means protection from the elements that helps avoid costly and time-consuming joint sanding. Each panel is third-party certified for quality and is rated for Exposure 1 bond durability for protected applications and limited exposure during normal construction delays.

Available Sizes (sized for 4' x 8')

Square Edge	3'-11 7/8" (1.216 m) x 7'-11 7/8" (2.435 m)
Tongue & Groove	3'-11 1/2" (1.206 m) x 7'-11 7/8" (2.435 m)

Building Code Performance Categories, Panel Thickness

- 19/32 CAT, 0.578" (14.68 mm)
- 23/32 CAT, 0.703" (17.85 mm)

Specifications

Length/Width Tolerance	± 1/16" (± 1.6 mm)
Straightness Tolerance	± 1/16" (± 1.6 mm)
Squareness Tolerance	± 1/8" (± 3.2 mm)
Testing Agency	APA®–The Engineered Wood Association
Classification	**Exposure 1** – OSB suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of mositure on structural performance as may occur due to construction delays, or other conditions of similar severity.
Code Fire Classification	Class III or C
Flame Spread Rating	76-200, smoke-developed index <450
Building Code Compliance	PS 2-18; CAN/CSA-0325-21

Other Information

Forestry Certification	DryGuard® Enhanced OSB panels are made in compliance with the Sustainable Forestry Initiative® (SFI®) SFI-00007 in the USA and Canada.
Product Warranty	DryGuard® Enhanced OSB is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at **www.buildgp.com**.

SUSTAINABLE FORESTRY INITIATIVE SFI-00007

Georgia-Pacific
DryGuard®
Enhanced OSB

buildgp.com

International Shipping

To prevent the introduction and spread of plant pests, **ISPM 15: International Standards for Phytosanitary Measures**, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance.

Pallets made with engineered wood, including DryGuard® Enhanced OSB, are exempt from ISPM 15 regulations. This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing", **www.PerformancePanels.com**).

Formaldehyde Emissions

DryGuard® Enhanced OSB contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the **Composite Wood Air Toxic Control Measure (ATCM)** and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the **Manufactured Home Construction and Safety Standards**.

Manufacturing Locations

Location	APA Mill Number	Zip Code	Harvest Radius
Allendale, SC	531	29827	50 miles
Fordyce, AR	475	71742	100 miles

DryGuard, Georgia-Pacific and the DryGuard and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. APA is a registered trademark of APA-The Engineered Wood Association. Sustainable Forestry Initiative, SFI, and the SFI logo are trademarks of Sustainable Forestry Initiative, Inc.
©2026 Georgia-Pacific Wood Products LLC. All rights reserved. WD-DGU-US-USCA-EN-1-R01-102026