



# BlueRibbon®

Rated Sheathing

[buildgp.com](http://buildgp.com)

**BlueRibbon® Rated Sheathing** is an excellent oriented strand board (OSB) choice for floor, wall and roof sheathing in residential and light commercial construction applications. Each panel is third-party certified for quality and is rated for Exposure 1 bond durability for protected applications and limited exposure during normal construction delays. BlueRibbon Rated Sheathing is edge coated to limit absorption and pick-up of moisture.

## Available Sizes\*

### Square Edge

3'-11<sup>7</sup>/<sub>8</sub>" (1.216 m) x 7'-11<sup>7</sup>/<sub>8</sub>" (2.435 m) - sized for 4' x 8'  
 3'-11<sup>7</sup>/<sub>8</sub>" (1.216 m) x 8'-11<sup>7</sup>/<sub>8</sub>" (2.740 m) - sized for 4' x 9'  
 3'-11<sup>1</sup>/<sub>2</sub>" (1.206 m) x 9'-11<sup>7</sup>/<sub>8</sub>" (3.044 m) - sized for 4' x 10'

### Tongue & Groove

3'-11<sup>1</sup>/<sub>2</sub>" (1.206 m) x 7'-11<sup>7</sup>/<sub>8</sub>" (2.435 m) - sized for 4' x 8'  
 3'-11<sup>1</sup>/<sub>2</sub>" (1.206 m) x 8'-11<sup>7</sup>/<sub>8</sub>" (2.740 m) - sized for 4' x 9'  
 3'-11<sup>1</sup>/<sub>2</sub>" (1.206 m) x 9'-11<sup>7</sup>/<sub>8</sub>" (3.044 m) - sized for 4' x 10'

\*Custom panels up to 26' are also available.

## Building Code Performance Categories, Panel Thickness

- 7/16 CAT - 0.418" (10.61 mm)
- 15/32 CAT - 0.451" (11.45 mm)
- 1/2 CAT - 0.483" (12.26 mm)
- 19/32 CAT, 0.578" (14.68 mm)
- 23/32 CAT, 0.703" (17.85 mm)
- 1-1/8 CAT - 1.091" (27.71 mm)

## Specifications

|                          |                                                                                                                                                                                                                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Length/Width Tolerance   | ± 1/16" (± 1.6 mm)                                                                                                                                                                                                                                                                       |
| Straightness Tolerance   | ± 1/16" (± 1.6 mm)                                                                                                                                                                                                                                                                       |
| Squareness Tolerance     | ± 1/8" (± 3.2 mm)                                                                                                                                                                                                                                                                        |
| Testing Agency           | APA®-The Engineered Wood Association                                                                                                                                                                                                                                                     |
| Classification           | <b>Exposure 1</b> - Rated sheathing suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity. |
| Code Fire Classification | Class III or C                                                                                                                                                                                                                                                                           |
| Flame Spread Rating      | 76-200, smoke-developed index <450                                                                                                                                                                                                                                                       |
| Building Code Compliance | PS 2-18; CAN/CSA-0325-21                                                                                                                                                                                                                                                                 |

## Other Information

**Forestry Certification** BlueRibbon® Rated Sheathing is made from wood sourced through a system that is third-party certified to the Sustainable Forestry Initiative® procurement standard.





**BlueRibbon®**  
Rated Sheathing

[buildgp.com](http://buildgp.com)

#### NGBS Green Certified

See our BlueRibbon® Rated Sheathing Sustainability Fact Sheet available at [www.buildgp.com](http://www.buildgp.com) for more information on potential point contributions towards specific green building programs.

#### NGBS Green Certified

BlueRibbon® Rated Sheathing is Home Innovation NGBS Green Certified for Resource Efficiency and Indoor Environmental Quality. Please visit [Homeinnovation.com/Green](http://Homeinnovation.com/Green) for more information.



#### Product Warranty

BlueRibbon® Rated Sheathing is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at [www.buildgp.com](http://www.buildgp.com).

#### International Shipping

To prevent the introduction and spread of plant pests, **ISPM 15: International Standards for Phytosanitary Measures**, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance.

**Pallets made with engineered wood, including DryGuard® Enhanced OSB, are exempt from ISPM 15 regulations.** This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: “Boxes, Crate and Reel Manufacturing”, [www.PerformancePanels.com](http://www.PerformancePanels.com)).

#### Formaldehyde Emissions

BlueRibbon® Rated Sheathing contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the **Composite Wood Air Toxic Control Measure (ATCM)** and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the **Manufactured Home Construction and Safety Standards**.

#### Manufacturing Locations

| Location           | APA Mill Number | Zip Code | Harvest Radius |
|--------------------|-----------------|----------|----------------|
| Brookneal, VA      | 451             | 24528    | 100 miles      |
| Clarendon, SC      | 532             | 29001    | 80 miles       |
| Englehart, ONT, CA | 530             | P0J 1H0  | 50 miles       |
| Fordyce, AR        | 475             | 71742    | 100 miles      |
| Hosford, FL        | 500             | 32334    | 75 miles       |

BlueRibbon, Georgia-Pacific and the BlueRibbon and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. APA is a registered trademark of APA-The Engineered Wood Association. Sustainable Forestry Initiative, SFI, and the SFI logo are trademarks of Sustainable Forestry Initiative, Inc. The Home Innovation NGBS Green Certified logo is a trademark of Home Innovation Research Labs. ©2026 Georgia-Pacific Wood Products LLC. All rights reserved.  
082026 Lit. Item # 512105