





INSTALLATION GUIDE



PRODUCTS


 Georgia-Pacific
DensDeck[®]
Roof Board

 Georgia-Pacific
DensDeck[®]
Prime Roof Board

 Georgia-Pacific
DensDeck[®]
ProFast[™]
Prime Roof Board

 Georgia-Pacific
DensDeck[®]
StormX[™]
Prime Roof Board

INSTALLATION INSTRUCTIONS



Georgia-Pacific redefined roof boards in 1987 with DensDeck® Roof Board. This innovative cover board provides stronger puncture protection and is non-combustible as a result of its gypsum core and fiberglass facers. Since 1987, Georgia-Pacific has continued innovating industry-leading, high-performance roof boards.

The Portfolio of DensDeck® Roof Boards offers options with even more strength and enhanced moisture resistance for adhered roofing assemblies.

Follow these instructions to install DensDeck® Roof Boards, DensDeck® Prime Roof Boards and DensDeck® ProFast™ Prime Roof Boards on any building in need of tough roofing defense. Always wear personal protective equipment (PPE) when working on construction projects to prevent onsite hazard.



Tools Needed

- Knife
- Cutting gloves
- Measuring tape
- Straight edge or T-square and/or chalk line
- Appropriate equipment to apply adhesive or install fasteners, per design and system manufacturer specification

Storage

- 1 Remove plastic packaging immediately upon receipt. (Any protective, plastic factory packaging that is used to wrap DensDeck® Roof Board Products for shipment is intended to provide only temporary protection from moisture exposure during transit and is not intended to provide protection during storage after delivery.)
- 2 Store boards outside, level and off the ground. Protect with a waterproof covering.
- 3 Provide means for air circulation around and under stored bundles.
- 4 Use adequate supports to keep the bundles flat, level and dry.



CAUTION: For product fire, safety and use information, go to buildgp.com/safetyinfo.

Handling

- 1 Measure and mark the board to size as needed. Score along mark and snap to break clean, then use a sharp knife to cut the back mat.
- 2 Carry DensDeck® Roof Board Products in an upright position.

Laying the Board

- 1 For a cover board application, lay the board down in a running bond pattern, offsetting the roof board joints from the underlying insulation joints.
- 2 Butt all board edges and ends tightly together*.
- 3 When added to a structural metal deck in a roof board application, support the edges by installing the edge joints on and parallel to the top flutes.

* DensDeck® Roof Board Products of any thickness do not require gapping.



Fastening

- 1 Refer to system manufacturer and FM Global requirements for fastener type and spacing, or adhesive installation requirements.
- 2 Grid marks on the board are 150 mm (6 inches) on center as a reference guide for the installer.

Transition from Roof to Wall

- 1 For a parapet wall, install DensDeck® Roof Board Products directly to the framing per specification and code requirements.
- 2 If the parapet kicker or cant strip is attached to the parapet wall framing, install the specified board from the Portfolio of DensDeck® Roof Boards over a solid substrate, rather than directly onto the slanted wall / roof framing.

Limitations

- 1 Refer to the Portfolio of DensDeck® Roof Boards Technical Guide (available at DensDeck.com) for additional installation instructions and important information concerning recommendations and limitations for use. Failure to adhere to such recommendations and limitations may void the limited warranty provided by Georgia-Pacific Gypsum for DensDeck® Roof Board Products.
- 2 Protect any of your DensDeck® Roof Board Products from moisture before, during and after installation. Although DensDeck® Roof Board Products are engineered with fiberglass facings and high-density gypsum cores, the presence of moisture can have a detrimental effect on the performance of the product and the installation of roofing membranes.
- 3 Georgia-Pacific Gypsum does not warrant and does not provide specifications or instructions for any specific assembly or system using DensDeck® Roof Board Products or any component in such assemblies or systems other than DensDeck® Roof Board Products.
- 4 Consult with the appropriate system manufacturer and/or design authority for system specifications and instructions and for specific instructions for applying other products to DensDeck® Roof Board Products.



Georgia-Pacific

DensDeck®
Roof Board



GP Gypsum LLC
133 Peachtree Street, N.E. | Atlanta, Georgia 30303

DensDeck.com
GP Tech Hotline: 800-225-6119

CAUTION: For fire, safety and use information, go to buildgp.com/safetyinfo.
WARRANTY: For current limited warranty for these products, visit buildgp.com/resources.

©2025 Georgia-Pacific Gypsum. All rights reserved. Unless otherwise noted, all trademarks are owned by or licensed to GP Gypsum LLC. Rev 08/25 Lit#: 623062

 Georgia-Pacific
DensDeck®
Roof Board