

Specifications

DryPly® plywood Sturd-I-Floor® panels are ideal for residential and light commercial construction, and provide outstanding performance for sub-floors. They have a water-repellent coating to provide weather protection during the normal exposed construction cycle*, and add proven performance and durability to new homes, room additions and renovations.

Available Sizes (Sized for 4' x 8')

Square Edge	3'-11 ⁷ %" (1.216 m) x 7'-11 ⁷ %" (2.435 m)
Tongue & Groove	3'-11½" (1.206 m) x 7'-11 ⁷ %" (2.435 m)

Building Code Performance Categories, Panel Thickness

- 19/32 CAT, 0.578" (14.68 mm)
- 23/32 CAT, 0.703" (17.85 mm)

Specifications

Length/Width Tolerance	+0, -½6″ (+0, -1.6 mm)		
Straightness Tolerance	± ¹ /16" (±1.6 mm)		
Squareness Tolerance	±1%" (±3.2 mm)		
Primary Species	Southern Yellow Pine		
Water Repellent Coating	Wax emulsion based surface sealer		
Testing Agency	APA®-The Engineered Wood Association		
Classification	Exposure 1 – Plywood suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of mositure on structural performance as may occur due to construction delays, or other conditions of similar severity.		
Code Fire Classification	Class III or C		
Flame Spread Rating	76-200, smoke-developed index <450		
Building Code Compliance	PS 1-09		
Other Information			
Forestry Certification	DryPly plywood Sturd-I-Floor panels are made from wood sourced through a system that is third-party certified to the Sustainable Forestry Initiative [®] procurement standard.		
Green Building Programs	See our DryPly plywood <i>Sustainability Fact Sheet</i> available at <i>www.builditbetter.com</i> for more information on potential point contributions towards specific green building programs.		
NGBS Green Certified	DryPly plywood is Home Innovation NGBS Green Certified for Resource Efficiency and Indoor Environmental Quality. Please visit <i>Homeinnovation.com/Green</i> for more information.		
Product Warranty	DryPly plywood is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at <i>www.builditbetter.com</i> .		



Specifications

International Shipping To prevent the introduction and spread of plant pests, *ISPM 15: International Standards for Phytosanitary Measures*, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance. Pallets made with engineered wood, including DryPly® plywood, are exempt from ISPM 15 regulations. This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing", *www.PerformancePanels.com*) Formaldehyde Emissions DryPly plywood Sturd-I-Floor® panels contain no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the *Composite Wood Air Toxic Control Measure (ATCM)* and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the *Manufactured Home Construction and Safety Standards*.

Manufacturing Locations	Location	APA Mill Number	Zip Code	Harvest Radius
	Emporia, VA	230	23847	40 miles
	Madison, GA	404	30650	100 miles
	Prosperity, SC	329	29127	80 miles



Georgia-Pacific Wood Products 133 Peachtree St., N.E. Atlanta, GA 30303 800-284-5347 www.builditbetter.com DryPly and the DryPly and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. APA and Sturd-I-Floor are registered trademarks of APA-The Engineered Wood Association. Sustainable Forestry Initiative, SFI, and the SFI logo are trademarks of Sustainable Foresty Initiative, Inc. The Home Innovation NGBS Green Certified logo is a trademark of Home Innovation Research Labs.

©2016 Georgia-Pacific Wood Products LLC. All rights reserved. Rev. 2/16 GP-TM Lit. Item #621501.